

# Clarius®

## Clarius® PSU



The Clarius range of LED lighting Power Supply Units are IP67 rated, constant voltage designed to power the Clarius range of LED lighting products.

They feature a regulated 24V DC output supplying continuous full rated current to load. The universal mains input voltage allows the power supply to be used across a wide geographical area while the highly efficient switch mode design ensures low operating costs and cool running.

They are available in for power variants, providing enough power for multiple units as necessary.

MODEL	ALT-30-24	ALT-60-24	ALT-100-24	ALT-150-24
<b>Power:</b>	30W	60W	100W	150W
<b>Output:</b>	24V DC / 1.25A	24V DC / 2.5A	24V DC / 4.2A	24V DC / 6.25A
<b>Input:</b>	170-250V AC / 0.45A 50/60 Hz	170-250V AC / 0.85 A 50/60 Hz	170-250V AC / 1.25 A 50/60 Hz	170-250V AC / 1.25 A 50/60 Hz
<b>Rating:</b>	IP67	IP67	IP67	IP67
<b>Dimensions</b>	200 x 20 x 29mm L x W x H	150 x 44 x 63mm L x W x H	214 x 44 x 63mm L x W x H	214 x 44 x 63mm L x W x H
<b>Power Upto Either:</b>	2x IS8, IS9, VS-CW or 1x IM8, IM9, VM-CW	3x IS8, IS9, VS-CW or 2x IM8, IM9, VM0CW or 1x IL8, IL9, VL-CW	6x IS8, IS9, VS-CW or 3x IM8, IM9, VM-CW or 2x IL8, IL9, VL-CW or 1x IX8, IX9, VX-CW	9x IS8, IS9, VS-CW or 5x IM8, IM9, VM-CW or 3x IL8, IL9, VL-CW or 3x IX8, IX9, VX-CW

Please note GJD reserve the right to change the information within this document, without notice. **DSPSU-31-08-15**

[www.gjd.co.uk](http://www.gjd.co.uk) | [info@gjd.co.uk](mailto:info@gjd.co.uk) | +44 (0) 1706 363 998

Unit 2 Birch Business Park, Whittle Lane, Greater Manchester, Lancashire, OL10 2SX