

# 4K UHD LED

## PD322-4KLED

## 4K UHD LED Monitor

### PD322-4KLED

|                               |                                   |
|-------------------------------|-----------------------------------|
| Panel Type                    | 32" (16:9) 4K LED Backlit Monitor |
| Case Type                     | Metal                             |
| Maximum Resolution            | 3840 x 2160 @ 60Hz                |
| Active Display Area           | 698.4 (H) x 392.85 (V)            |
| Pixel Pitch                   | 0.181875 (H) x 0.181875 (V)       |
| Bezel Thickness               | L/R/U: 15.5mm, D: 23.1mm          |
| Contrast Ratio                | 3000 : 1                          |
| Brightness                    | 300 cd / m <sup>2</sup>           |
| Response Time                 | 5m.sec (G to G)                   |
| Viewing Angle                 | 178 /178 °                        |
| Display Colours               | 1.07B                             |
| Display Mode                  | Quad, Pip, Pop                    |
| Video Synchronisation         | Yes                               |
| PC Compatibility              | Yes                               |
| Aspect Ratio                  | 16:9 / 4:3                        |
| VGA Auto Frequency Correction | Yes                               |
| Speakers                      | 5W x 2                            |
| Number of Speakers            | 2                                 |
| Sound Demodulation            | ACC                               |
| Mute                          | Yes                               |
| Work Humidity                 | 5% – 90%                          |
| Work Temperature              | -10 to +50 °C                     |
| Volume +/- Power On/Off       | Yes                               |

### IN / OUT INTERFACE

|                    |   |
|--------------------|---|
| Video Interface    | 2 x HDMI v 2.0 input, 2 x DP v1.2 input |
| Audio              | PC audio out                            |
| Power Interface    | AC in                                   |
| Termination        | 75 ohm                                  |
| Certification      | CE, FCC, ROHS                           |
| VESA               | 200 x 200                               |
| Stand Type         | Desk                                    |
| Colour             | Black                                   |
| Button Position    | Bottom right                            |
| Packing Dimensions |   |
| Nett Weight        | 12.8 Kgs                                |
| Gross Weight       | 11.5 Kgs                                |



### POWER

|                   |                   |
|-------------------|-------------------|
| Power Supply      | N/a               |
| Voltage           | 110 / 230v AC     |
| Power Consumption | 60 watt (typical) |

### OSD CONTROLS

Brightness, Contrast, Eco, DCR, H.Position, V. Position, Clock, Phase, Aspect, Colour Temp, OSD setting, OSD language, OSD H. Pos, OSD V. Pos, OSD timer, OSD Transparency, Factory Reset, Singal Source, Volume

### OSD LANGUAGE

English, French, German, Chinese, Italian, Spanish, Portuguese, Turkish, Polish and Dutch.

### ACCESSORIES

Remote, power cable, HDMI cable, User's manual

