

MC2-WE



The first line of defence

Perimeter protection that alerts anyone to the opening of doors & windows

Perimeter protection just added another dimension with the MC2-WE. The wireless magnetic contact offers the ultimate ease of installation, with superior security for the perimeter protection any property deserves.

Please Note: Magnet included

www.pyronix.com

MC2-WE



Adaptable, optimised & stylish

• Fit where required with two reed switches

A reed switch is positioned on the top and side of the contact to allow the MC2-WE to be fitted horizontally or vertically.

• 300m range

The high sensitivity receiver allows a wireless signal range of up to 300m in open space, eliminating the need for repeaters and reducing installation costs.

• Different colours available

Pick from either white or brown (MC2BROWN-WE) to deliver the desired look.

Faster installation, less invasion, upsell opportunities & the same superior security with two-way wireless technology

• No wires, no fuss

As the system is fully wireless there is no need to run wiring by lifting floorboards or moving furniture, saving you time and money.

• One-Push-To-Learn



A feature in all Enforcer wireless devices that means learning them onto the system can be done in seconds. A simple one button learning feature for easy installation.

• Signal Strength Indicators (SSI)

SSI in all Enforcer wireless devices allow them to be optimally positioned during installation, without the need to refer back to the panel.

• Self-aware sensors

The sensor will tell the control panel when it has low battery, is in fault, or has failed supervision. The sensors provide the information the control panel needs to ensure it stays safe and secure.

Partcode	MC2-WE
Inputs	
Magnetic contact and one channel universal transmitter	✓
Key Features	
Terminal for N/C input and reed switch	✓
Tamper input	✓
Front and rear tamper protection	✓
Signal Strength Indicators (SSI)	✓
Magnet included	✓
Electrical Specifications	
Transmission frequency	868MHz, FM transceiver
Transmission method	128bit encrypted radio protocol
Range in open space	1600m
3V lithium battery included	1 x CR2
Minimum battery life (years)	2
Warranty	2 years
Certifications	
Electrical conformity	CE
EN50131	Grade 2
Environmental class	II
	CA12.01326
	IMQ Test House

Beat the burglar with tamper protection

This ensures that maximum security is maintained against accidental or malicious tampering of the system, providing that added peace of mind that the system is secure.

Expand the system with an input

Through the MC2-WE, an extra input can be added to the security system to add any other device that the installation requires.

Meet the required security standard with Grading options

The MC2-WE is Grade 2 for the superior security the installation needs.